

DOT9100 BASE SURFACE MOUNT SERIES 2



High Performing stylish LED system designed to suit commercial and high end residential spaces

Narrow Beam – 33° Beam Angle & Wide Beam – 70° Beam Angle Reflectors

CRI 80 , 3 Macadam steps, 350mA ,15.1 watts, 3000k or 4000k

Standard Dimming Options Available – DALI or Phase dimming

350mA driver option, CRI 80 , 51,000hrs L90

Multiple AX-Lock accessories available

Patented Easy installation / removal clip system

99.99% pure aluminium reflectors designed for the DOT9100 series 2

Dedicated Heat Sink with excellent thermal performance

DOT9100 BASE SURFACE MOUNT SERIES 2

Product Specification

100000 Rated Average Life	IP20 Ingress Protection Rating	IK00 Impact Rating	14.2W System Power	240V Voltage
0.8KG Weight	4000K CCT	1417Lm Exit Lumen	White Luminaire Colour	Powder Coated Finish

Item Code	Description	Dimming Technology	Beam Angle
9134SB4	9134 BASE SM 14W 4K 80 NAR IP20 NON DIM	Non - Dimmable	40°
9138SB4D1	9138 BASE SM 14W 4K 80 WIDE IP20 DALI DIM	DALI	70°
9138SB4	9138 BASE SM 14W 4K 80 WIDE IP20 NON DIM	Non - Dimmable	55°
9134SB4D1	9134 BASE SM 14W 4K 80 NAR IP20 DALI DIM	DALI	40°

LINE DRAWINGS

